



KONICA MINOLTA

The bizhub PRESS C1060 is purpose-built to work as hard as you do – delivering spectacular image quality at a fraction of the cost of offset equipment. You will have 60 ppm output to keep ahead of tight deadlines, SEAD IV image processing to achieve smoother edges and superb colour density, and your choice of exclusive Konica Minolta or industry-standard Fiery or Creo\* image control options to meet any production need. Auto finishing options include stapling, saddle-stitching, six folding patterns, perfect binding, even GBC hole-punching and in-line ring binding to meet any job specs. And Konica Minolta's internal IC-602 Image Controller is custom-designed for high-speed printing, editing and job queue management. Want greater power, higher reliability and superior performance in a smaller footprint? Count on the bizhub PRESS C1060.



# SUPERIOR COLOUR, POWERFUL FINISHING, AFFORDABLE COST



## bizhub PRESS C1060

COLOUR PRODUCTION PRINTER/COPIER/SCANNER

- 60 PPM OUTPUT FOR HIGH-VOLUME COLOUR PRINT PRODUCTION
- SIMITRI™ HD<sup>F</sup> TONER WITH BIOMASS TO PROTECT THE ENVIRONMENT
- SEAD IV SCREEN-ENHANCING ACTIVE DIGITAL PROCESSING SYSTEM
- REAL-TIME IMAGE DENSITY AND COLOUR DENSITY ADJUSTMENTS
- ENHANCED DE-CURLING FUNCTION FOR CHALLENGING STOCKS
- 7,500-SHEET PAPER CAPACITY, AUTO DUPLEX UP TO 300 GSM
- AIR-SUCTION PAPER FEED OPTION FOR RELIABLE PAPER HANDLING
- A WIDE RANGE OF FINISHING OPTIONS TO HANDLE ANY JOB SPECS
- 100-SHEET STAPLING, 200-PAGE BOOKLETS, 600-PAGE BOUND BOOKS
- IN-LINE GBC PUNCHING UNIT, IN-LINE RING BINDER UNIT
- 5,000-SHEET STACKER OPTION – CONNECT 2 FOR 10,000-SHEET RUNS
- CUSTOM KONICA MINOLTA IC-602 IMAGE CONTROLLER OPTION
- POWERFUL FIERY® AND CREO® IMAGE CONTROLLER OPTIONS

\*Not available at time of launch





**SPECIFICATIONS**

Print/Copy Process	Laser Electrostatic Process
Development System	Dry Dual Component Magnetic Brush Development
Print Speed / Monthly Duty Cycle	60 ppm / 300,000
Resolution / Gradation	1200 x 1200 dpi / 256 8-bit CMYK
Standard Memory / * Optional Memory	4 GB Image Memory; 6 GB System Memory
Warm-up Time	Approx. 6.5 minutes
Print/Copy Quantity	1-9,999 (Countdown, Interrupt Capability)
Magnification	Zoom Range: 25%-400%
* Original Size	Optional Reversing Duplexing Document Feeder: up to 11" x 17" maximum / 100 Sheets / Mixed Original Detection
Paper Size / Paper Weight	All trays: up to 13" x 19.2" maximum / up to 256 gsm; Tray 3 (LU-202) and Tray 4 Lower Tray (PF-602m): up to 300 gsm
Standard Paper Supply / Paper Capacity (max.)	Tray 1: 500-sheet, Tray 2: 1,000-sheet / 7,500 sheets maximum
Power Requirements (Engine)	208-240 V, 60 Hz, 22 A Dedicated Line
Dimensions (W x D x H) / Weight	29.9" x 39.1" x 42.3" (Engine only) / 642 lb. (Engine only)
Colour Modes / Exposure Modes	Auto, Full Colour, B&W, Single Colour, Text, Text/Photo (Clear Text & Halftones), Photo Image, Map (Fine Edges, Text)
Available Functions	Auto Zoom, Auto Paper Select, Auto Low Power, Auto Reset, Auto Shut Off, Colour Mode, Combine Originals, Copy Density, Cover Sheet Feeding, Custom Size Paper Setting, Folding, Frame, Center Erase, Image Centering, Image Repeat, Interrupt Copying, Job List, Manual Shut Off, Mode Memory, Non-Image Area Erase, Page Margin, Power Save, Proof Copy, Remote Monitor, Reserve Job, Rotation, Separate Scan Mode, Simplex, Duplex, Stamp, Staple, Tab Paper, Trimming, Weekly Timer, Z-Folded Original Setting, Zoom
* Available Options	FD-503 Multi-Fold Punch Unit, FS-531 50-Sheet Staple Finisher, FS-532 100-Sheet Staple Finisher, FS-612 Booklet Finisher, GP-501 GBC Multi-Hole Punch, GP-502 In-line Ring Binder, HM-102 Paper Humidifier, HT-503 Dehumidifier Heater (for LU-202), HT-504 Dehumidifier Heater (for PF-602m), HT-506 Dehumidifier Heater (for PF-707), LC-501 Cart (for LS-505), LS-505 Large Capacity Stacker, LU-202 2,500-Sheet Paper Feed Unit, MK-732 Post-insert Mount Kit (for FS-532), PB-503 Perfect Binder Unit, PI-502 Post Insert, PF-602m 6,000-Sheet Paper Feed Unit, PF-707 Vacuum Paper Feed Unit, PK-512 Punch Kit, PK-522 2/3-hole Punch (for FS-532), RU-509 Relay Unit, RU-510 Relay Unit (for GP-501), SD-506 Saddle-Stitch Unit, SD-510 Saddle-Stitch Kit (for FS-532)

**• IC-602 INTERNAL KONICA MINOLTA IMAGE CONTROLLER (OPTIONAL)**

System Version / Operating System	Konica Minolta 2.0 / TimeSys Linux 6.1
Processor / Memory / Hard Disk Drive	Intel® Pentium G850 2.9 GHz; 8 GB / 500 GB x 3
Engine	I/F Serial 768 Kbps, C1070 Series Video Clock (Print): 56.135 MHz
Page Description Language / PDF Support	Adobe® PostScript®, CPSI 3019, TIFF, PCL 5c/6, XPS / PDF v1.7, PDF/X-1a, PDF/X-3
Variable Data Handling	PPML 2.2
Font Support	Adobe Roman: 136 fonts, PCL: 81 fonts
OS Support (for IC-602)	<b>PS Plug-in:</b> Windows XP, Windows Vista, Windows 7, Windows 8, Windows Server 2003, Windows Server 2008, Windows Server 2012; <b>Mac OS X</b> 10.5, 10.6, 10.7, 10.8 <b>PS PPD:</b> Windows XP, Windows Vista, Windows 7, Windows 8, Windows Server 2003, Windows Server 2008, Windows Server 2012; <b>Linux CUPS</b>
Applications	PageScope Direct Print, PageScope EMS Plug-in, PageScope Web Connection, PageScope Account Manager, PageScope Net Care Device Manager, Net Backup Tool, Font Management Utility, Print Status Notifier, Print Utility for UNIX, Job Centre (Job Control/Editing Utility), Color Centre (Colour Management Utility), Printgroove POD Queue
Power Supply	100-240 V, 50-60 Hz

**• IC-308 EXTERNAL FIERY IMAGE CONTROLLER (OPTIONAL)**

Operating System / Processor / Memory	Windows 7 Professional 64-bit / Intel® Core™ i5-2400 3.1 GHz Processor (up to 3.4 GHz with Turbo Boost) / 4 GB RAM
Hard Disk Drive / DVD Drive	1 TB HDD / Internal DVD-RW Drive
Software	Fiery System FS100 Pro
Networking Connectivity	Simultaneous Auto Switching Protocols, EtherTalk II, TCP/IP, Novell iPX iPrint, LDAP Support (Exchange, Novell, Domino, LDAPv3/RFC2251), Email Address Access and Authentication, User Password Validation, Certificate Management (SSL/TLS, X509 Standard), IP Sec Support, IPv6 Support
File Format Support	Adobe® PostScript®, Adobe PDF 1.5 to 1.7 (Adobe Acrobat® 6 to 9), PDF/X-1a, 3 and 4, Encapsulated PostScript (EPS), MS Office: DOC, XLS, PPT, PUB (via Hot Folders)
* Optional File Format Support	JPEG, DCS 2.0, CT/LW, 1-bit TIFF, TIFF, TIF/IT, PDF2Go
SNMP Printing Support	Bonjour, SMB (peer-to-peer), LPD
Performance Features	Fiery Smart RIP, RIP-While-Print, RIP 1-While-Print 2, Fiery RIPChips™, EFI Video Interface Card, ECT Compression (for flexible compression ratios and visually lossless image quality)
Fiery Utilities	Fiery Bridge 1.2, Fiery Command WorkStation 5, Fiery Driver, Fiery Graphic Arts Package, Fiery Hot Folders, Fiery Remote Scan, Fiery WebTools™, Fiery Workflow (Central, JDF), Spot-On
* Fiery Options	Fiery SeeQuence Suite (Fiery SeeQuence Impose, Fiery SeeQuence Compose, Fiery SeeQuence Preview), Fiery Graphic Arts Package (Premium Edition), ES-2000 Spectrophotometer, Fiery Color Profiler Suite, Removable Hard Disk Drive, Fiery Integrated Workstation: Fiery Stand, GUI Kit (19" Display, Keyboard, Mouse)
* Optional Variable Data Handling	FreeForm™ 2, PPML 2.2 (PODI certified), Creo VPS Compatible, Optimized PostScript® and Optimized PDF
Power Supply / Dimensions (W x H x D)	100-240 VAC @ 50-60 Hz, 6 A @ 100 VAC, 3 A @ 240 VAC / 8.4" (W) x 19.2" (H) x 14" (D)

**• IC-309 EXTERNAL CREO IMAGE CONTROLLER (OPTIONAL)\***

Operating System / Processor / Memory	Microsoft Windows® Embedded Standard 7 (WES 7) x64 bit / Intel® Core i5-3550S Processor 3.0 GHz up to 3.7 GHz with Turbo Boost, Quad Core 6 GB Total Memory (3 GB System RAM; 3 GB Image Memory)
Hard Disk Drive / DVD Drive	3 x 1 TB Hard Disc Drive / Internal DVD-RW
Standard Hardware	Keyboard, Mouse and 22" Monitor
* Optional Hardware	Creo Colour Server product stand, X-Rite i1 Spectrophotometer
Software Support	Adobe Acrobat 9.0 Standard, Enfocus, PitStop Acrobat Plug-in Lite Version 8
Networking Connectivity	Ethernet 1000BASE-T/100BASE-TX/10BASE-T, TCP/IP, IPv4/IPv6, NetBEUI, AppleShare (File Sharing), PAP (File Printing), NetBIOS, 802.1x Authentication
Page Description Language	PS, EPS, PDF 1.8 (CPSI 3017), TIFF, JPEG (excluding progressive JPEG and JPEG 2000), IPDS (Transaction Power Kit only)
Hybrid Workflow	PDF/X-1a, JDF 1.3
Variable Data Handling	PML 2.2, VPS (Creo Variable Print Specification 1.5)
Supported Print Standards	PDF 9, ICC v4, Pantone Goe, FograCert, Adobe PDF Print Engine (APPE) 2 via a special software update
New Functions	Destination Profiles to Spot Colours, Pantone Goe Library, Colour Sets, Print Colour Sets, Office Hot Folder Tool, Remote Site Manager, JDF 1.3 connectivity, Creo Colour Server Job Ticket Software, Bi-directional Integration with Kodak Prinergy and Agfa Apogee, Easy VDP (Variable Data Printing), File Creator, Improved Perfect Binder Support
* Optional Power Kits	Professional Power Kit, Process Power Kit, Imposition Power Kit, Transaction Power Kit
Power Supply / Dimensions (W x H x D)	100-240 VAC, 50-60 Hz, 7 A-3.5 A / 17.6" (W) x 7.2" (H) x 22" (D)

**• IC-415 INTERNAL FIERY IMAGE CONTROLLER (OPTIONAL)**

Operating System / Processor / Memory	Linux 32-bit / Intel® Pentium G850 2.9 GHz Processor / 2 GB RAM
Hard Disk Drive / DVD Drive	500 GB SATA / None
Software	Fiery FS100
Networking Connectivity	TCP/IP, AppleTalk, Point and Print, Bonjour Support, Port 9100 (w/BID), IPP, FTP, SMB, Email client, Print via Email (PS/PDF), Network Time Protocol, IPv6 Support
Page Description Language	Adobe® PostScript®, Enhanced PCL 6/PCL 5
Variable Data Handling	FreeForm™ 2, Record & Set Level Finishing Support, VDP Record Range Printing, Define Record Length
Security	Data Protection, Network Protection, User Authentication
Fiery Utilities	Fiery Bridge 1.2, Fiery Command WorkStation 5, Fiery Driver, Optional Fiery Embedded Productivity Package, Optional Fiery Hot Folders, Fiery Remote Scan, Fiery WebTools™

● OPTIONAL ● STANDARD

\*Not available at time of launch.

Konica Minolta Optimized Print Services offers a full suite of device output services and workflow solutions that increase efficiency and control costs. Please contact your authorized Konica Minolta sales representative for details.

© 2014 KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA logo, Count on Konica Minolta, bizhub PRESS and PageScope are registered trademarks or trademarks of KONICA MINOLTA, INC. Trademarks of the Canadian Breast Cancer Foundation, used under licence. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. Design and specifications are subject to change without notice. Some functions may require options, which may or may not be available at time of launch.



KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD.  
369 Britannia Road East  
Mississauga, ON L4Z 2H5  
www.konicaminolta.ca